

## MOSA GE 10000 BES/GS



### Specifications

<b>A.C. GENERATION</b>	<b>50 Hz, synchronous, three-phase, self-excited, self-regulated</b>
*Three-phase generation (stand-by)*	11 kVA (8.8 kW)/ 400 V / 15.9 A
*Three-phase generation (P.R.P)	10 kVA (8 kW)/ 400 V / 14.4 A
Single-phase generation	6 kVA / 230 V / 26 A
Duty cycle	100%
Power factor (cos φ)	0.8
Insulation class	H
* Output according to ISO 8528-1	
<b>ENGINE</b>	<b>Diesel, 4-stroke, air cooled</b>
Type	Honda GX 620
Output*	13.3 kW (18 HP)
Speed	3000 rpm
Displacement	614 cm <sup>3</sup>
Cylinders	2
Fuel consumption	313 g/kWh
* Maximum output according to ISO 3046/1	
<b>GENERAL SPECIFICATIONS</b>	
Tank capacity	18 l
Running time (Load 75%)	6 h
Protection	IP 23
Dimensions L x w x h (mm) *	910x525x620
Weight *	133 kg
Noise level	99 LWA (74 dB(A) - 7 m)
* Dimensions and weight without trolley/trailer.	



# AmoraSub

[www.amorasub.pt](http://www.amorasub.pt)

Parque Industrial S. Marta  
de Corroios  
Rua Manuel Ribeiro, Lote 13  
2845-409 Amora - Portugal

T +351 919 708 279  
E [geral@amorasub.pt](mailto:geral@amorasub.pt)