

MOSA GE 9000 DS



Specifications

A.C. GENERATION	50 Hz, asynchronous, three-phase, self-excited, self-regulated, brushless
Three-phase generation	8 kVA (6.4 kW) / 400 V / 11.5A
Single-phase generation	6 kVA/ 230 V / 26A
Duty cycle	100%
Power factor (cos φ)	0.8
Insulation class	H
ENGINE	Diesel, 4-stroke, air cooled
Type	Ruggerini MD 190
Output*	11.5 kW (16 HP)
Speed	3000 rpm
Displacement	851 cm ³
Cylinders	2
Fuel consumption	230 g/kWh
* Maximum output according to ISO 3046/1	
GENERAL SPECIFICATIONS	
Tank capacity	9 l
Running time (Load 75%)	4.5 h
Protection	IP 23
Dimensions L x w x h (mm) *	1050x530x630
Weight *	170 kg
Noise level **	100 LWA (75 dB(A) - 7 m)
* Dimensions and weight inclusive of all parts without wheels and towbar. ** LWA conforms to EEC Directive 536	



AmoraSub

www.amorasub.pt

Parque Industrial S. Marta
de Corroios
Rua Manuel Ribeiro, Lote 13
2845-409 Amora - Portugal

T +351 919 708 279
E geral@amorasub.pt