

STANLEY HP10



The HP10 hydraulic power unit is designed for continuous duty operation of any hydraulic tool in the EHTMA category of C, D and E. The HP10 provides world class cooling in a compact powerful unit.

SPECIFICATIONS

Output Capacity	20 ~ 40 LPM (EHTMA CAT C~E)
Pressure	138 Bar (2000 Psi)
Circuit Type	Open Centre
Connectors / Size	See ordering information
Hydraulic Capacity	11.4 Litres
Fuel Tank Capacity	20.8 Litres
Engine Oil Capacity	1.4 Litres
Engine Type	B&S 18 HP Vanguard OHV
Starting System	12v Battery Start
Fuel Type	Unleaded Petrol
Weight	150 Kg (Wet)
Dimensions LxWxH	89 x 55 x 74cm

FEATURES:

- EHTMA Category C, D and E hydraulic circuit with superior cooling.
- Tool circuit lockout during start up – safety feature.
- Lift & Latch handle with fold-up side handles
- Quartz hour meter on control panel records engine run time.
- 35-AH sealed, non-spillable, no maintenance battery located in covered compartment.
- In tank hydraulic filter with dipstick and easy access filter replacement.



AmoraSub

www.amorasub.pt

Parque Industrial S. Marta
de Corroios
Rua Manuel Ribeiro, Lote 13
2845-409 Amora - Portugal

T +351 919 708 279
E geral@amorasub.pt